


Figure C4. PLOTS of 'Formula Distance' - 'Carey Service Contour Distance' as a function of height for various ERP's










Figure C5. Basic VHF One-Way or Two-Way Service Contour Data.

Elevations Used: 100, 200, 500, 1000, 2000, 5000 ft.

30.5, 61.0 152.4, 304.8, 609.6, 1524 meters

ERP's Used: 50, 100, 250, 500, 750, 1000, 1400 watts

Matrix of Carey 37 dBu Service Contour Distances (km):

Elevations--->

$$VS = \begin{bmatrix} 14.001 & 18.668 & 27.037 & 35.245 & 46.027 & 57.454 \\ 16.093 & 21.565 & 30.899 & 40.073 & 51.499 & 63.408 \\ 19.473 & 26.071 & 36.693 & 47.154 & 59.385 & 71.777 \\ 22.37 & 30.095 & 41.682 & 52.948 & 65.822 & 78.053 \\ 24.14 & 32.509 & 44.74 & 56.649 & 69.524 & 81.916 \\ 25.75 & 34.44 & 47.315 & 59.224 & 72.26 & 84.652 \\ 27.52 & 36.854 & 50.051 & 62.443 & 75.317 & 88.031 \end{bmatrix}$$

Error Matrix for points in above matrix:
'Formula calculated distance' - 'Carey Service Contour Distance' (km):

$$E = \begin{bmatrix} 1.139 & 0.813 & 0.029 & -0.785 & -2.727 & -1.428 \\ 1.271 & 0.759 & 0.057 & -0.765 & -2.356 & -0.737 \\ 1.277 & 0.56 & 0.114 & -0.613 & -1.62 & 0.432 \\ 1.256 & 0.158 & -0.03 & -0.499 & -1.148 & 1.476 \\ 1.254 & -0.061 & -0.21 & -0.756 & -0.916 & 1.559 \\ 0.909 & -0.446 & -0.803 & -1.008 & -1.069 & 1.254 \\ 0.587 & -1.126 & -1.389 & -1.783 & -1.524 & 0.069 \end{bmatrix}$$

A row by row plot of these errors is presented in Figure C4.

Standard Deviation of Above Errors: $\sigma = 7.164$ km

Error Matrix -- FCC Proposed Equation:
'FCC equation distance' - 'Carey Service Contour Distance' (km):

EFCC =
$$\begin{bmatrix} -0.38 & -0.695 & -1.106 & -1.029 & -0.879 & 7.682 \\ -0.337 & -0.775 & -0.906 & -0.496 & 0.723 & 11.933 \\ -0.374 & -0.87 & -0.335 & 0.821 & 3.918 & 19.55 \\ -0.278 & -0.945 & 0.373 & 2.544 & 7.4 & 27.584 \\ -0.085 & -0.768 & 1.053 & 3.775 & 10.206 & 33.11 \\ -0.196 & -0.722 & 1.33 & 4.963 & 12.435 & 37.538 \\ -0.096 & -0.668 & 2.155 & 6.444 & 15.578 & 43.104 \\ \end{bmatrix}$$

Standard Deviation of errors for FCC Proposed Equation:

 $\sigma FCC = 79.901$ km

Figure C6. Proposed VHF One-Way or Two-Way Mobile Interference Formula.

The following formula has been developed for calculating VHF One-Way or Two-way Mobile Interference Contour Distances:

where

d is the radial distance in kilometers

h is the radial antenna HAAT in meters

p is the radial ERP in watts

Figure C7 contains a series of plots of the proposed formula.

Figure C8 contains a series of plots of the Carey Interference Contour (without the 3 dB/Octave height correction).

Figure C9 contains a series of plots of the Carey Interference Contour (with the 3 dB/Octave height correction).

Figure C10 contains a series of plots of the Carey Interference Contour (50/50 weighted average of the Carey Interf Contour w & w/o the 3 dB/Octave height correction).


Figure C11 contains a series of plots of the differences between the proposed formula results and the Carey Interference Contour for height up to 500'.

Figure C12 contains a series of plots that show the FCC proposed equation. These plots are included to illustrate the discontinuity contained in the FCC proposed equations. The equation used for these calculations was:

$$d=8.577 \times h \times p$$
 $h < 150 \text{ meters}$ $d=12.306 \times h \times p$ $h \ge 150 \text{ meters}$


Figure C13 contains listings of the Carey Interference Contour data, errors, and relevant results.

Figure C7. VHF MOBILE INTERFERENCE CONTOUR DISTANCES




VHF One-Way or Two-Way Mobile Interference Contour Distances as calculated from proposed formula as a function of Height for ERP's of 50, 100, 250, 500, 750, 1000, 1400 watts

Figure C8. VHF MOBILE CAREY INTERFERENCE CONTOUR DISTANCES




VHF One-Way or Two-Way Mobile Interference Contour Distances (without additional 3 dB/octave height correction above 500') as a function of Height for ERP's of 50, 100, 250, 500, 750, 1000, 1400 watts

Figure C9. VHF MOBILE CAREY INTERFERENCE CONTOUR DISTANCES




VHF One-Way or Two-Way Mobile Interference Contour Distances (with additional 3 dB/octave height correction above 500') as a function of Height for ERP's of 50, 100, 250, 500, 750, 1000, 1400 watts


Figure C10. VHF MOBILE CAREY INTERFERENCE CONTOUR DISTANCES




VHF One-Way or Two-Way Mobile Interference Contour Distances (50/50 weighted average w & w/o additional 3 dB/octave height correction above 500') as a function of Height for ERP's of 50, 100, 250, 500, 750, 1000, 1400 watts.

Figure C11. PLOTS of 'Formula Distance' - 'Carey Interf. Contour Distance' as a function of height up to 500' for various ERP's.










Figure C12(a). Plot of VHF Interference Distance From FCC Equation




Figure C12(b). Plot of VHF Interference Distance From FCC Equation




Figure C12(c). Plot of VHF Interference Distance From FCC Equation




Figure C12(d). Plot of VHF Interference Distance From FCC Equation




Figure C12(e). Plot of VHF Interference Distance From FCC Equation




Figure C12(f). Plot of VHF Interference Distance From FCC Equation




Figure C12(g). Plot of VHF Interference Distance From FCC Equation




Figure C13. Basic VHF One-Way or Two-Way Mobile Interference Contour Data

Elevations Used: 100, 200, 500, 1000, 2000, 5000 ft.

30.5, 61.0, 152.4, 304.8, 609.6, 1524 meters

ERP's Used: 50, 100, 250, 500, 750, 1000, 1400 watts

Matrix of Carey Interference Contour Ditances (km) up to 500' elevation:

Elevation -->

Matrix of Carey Interference Contour Distances (km) without 3 dB/Octave correction above 500' elevation:

Matrix of Carey Interference Contour Distances (km) with 3 dB/Octave correction about 500' elevation:

Error Matrix for points up through 500' elevation: 'Formula calculated distance' - 'Carey Interf Contour Distance' (km):

EIL =
$$\begin{bmatrix} 4.677 & 0.54 & -3.486 \\ 3.611 & 0.74 & -2.709 \\ 1.297 & 0.196 & -1.203 \\ -0.855 & -0.204 & 0 \\ -2.24 & -0.768 & 0.949 \\ -3.413 & -1.16 & 1.902 \\ -4.807 & -1.303 & 2.545 \end{bmatrix}$$

Standard Deviation of Above Errors: $\sigma = 10.658$ km["]

A row by row plot of these errors is presented in Figure C11.

Error Matrix for points aabove 500' elevation:
'Formula calculated distance' - 'Carey Interf w/o correction' (km):

ELU =
$$\begin{bmatrix} -6.849 & -6.997 & -0.235 \\ -4.663 & -3.676 & 5.326 \\ -0.565 & 1.451 & 16.335 \\ 2.465 & 6.125 & 26.413 \\ 4.49 & 9.265 & 33.566 \\ 5.861 & 11.938 & 39.086 \\ 8.145 & 15.243 & 45.611 \end{bmatrix}$$

Error Matrix for points above 500' elevation: 'Formula calculated distance' - 'Carey Interf w correction' (km):

Error Matrix for points above 500' elevation:
'Formula calculated distance' - '50/50 Weighted Average of Carey
Interf w & w/o Correction' (km):

$$EAU = \begin{bmatrix} -10.712 & -16.331 & -19.466 \\ -8.767 & -14.217 & -15.113 \\ -5.634 & -10.7 & -6.92 \\ -3.409 & -6.831 & 2.192 \\ -1.545 & -4.012 & 8.621 \\ -0.415 & -2.546 & 13.578 \\ 1.225 & -0.529 & 19.7 \end{bmatrix}$$

Error Matrix for all points from proposed equation re 50/50 weighted Average of Carey Interf w & w/o Correction (km):

$$\mathbf{EA} = \begin{bmatrix} 4.677 & 0.54 & -3.486 & -10.712 & -16.331 & -19.466 \\ 3.611 & 0.74 & -2.709 & -8.767 & -14.217 & -15.113 \\ 1.297 & 0.196 & -1.203 & -5.634 & -10.7 & -6.92 \\ -0.855 & -0.204 & 0 & -3.409 & -6.831 & 2.192 \\ -2.24 & -0.768 & 0.949 & -1.545 & -4.012 & 8.621 \\ -3.413 & -1.16 & 1.902 & -0.415 & -2.546 & 13.578 \\ -4.807 & -1.303 & 2.545 & 1.225 & -0.529 & 19.7 \end{bmatrix}$$

Standard Deviation of Above Errors: $\sigma A = 46.89$ km

NO ERROR MATRICES HAVE BEEN COMPUTED RE FCC EQUATIONS. Equations that contain a discontinuity as a function of height are not practical.

Figure D1. Proposed UHF One-Way or Two-Way Mobile Service Contour Formula.

The following formula has been developed for calculating UHF One-Way or Two-Way Mobile Service Contour Distances:

$$d = 2.024 \times h$$
 (0.331-0.0000021 x p) (0.171-0.0000034 x h)

where

d is the radial distance in kilometers

h is the radial antenna HAAT in meters

p is the radial ERP in watts

Figure D2 contains a series of plots of the proposed formula.


Figure D3 contains a series of plots of the Carey 39 dBu Service Contour Distances for the same points displayed in Figure D2.

Figure D4 contains a series of plots of the differences between the proposed formula results and the Carey Service Contour data.

Figure D5 contains listings of the Carey 39 dBu Service Contour data, errors, and relevant results. Errors for the FCC Proposed equation are also listed. The equation used for these calculations was:


$$d = 1.739 \times h \times p$$

Figure D2. UHF ONE-WAY OR TWO-WAY MOBILE SERVICE CONTOUR DISTANCE



UHF One-Way or Two-Way Mobile Service Contour Distances as calculated from proposed formula as a function of Height for EPS's of 50, 100, 250, 500, 750, 1000, 3500 watts

Figure D3. UHF 39 dBu Service Contour Distances



UHF One-Way or Two-Way 39 dBu Service Contour Distances as a function of Height for ERP's of 50, 100, 250, 500, 750, 1000, 3500 watts.

Figure D4. PLOTS of 'Formula Distance' - 'Carey Service Contour Distance' as a function of height for various ERP's

